

TENDER SCHEDULE FOR THE RENOVATION (TO PREVENT THE LEAKAGE) FOR KERALA STATE CO-OPERATIVE BANK BUILDING, REGIONAL OFFICE, THRISSUR.

Sl.No	Particulars	Qty	Unit	Rate		Amount
				figures	words	
				figures	words	
1	Re-Plastering: 12 mm cement plaster on the masonry wall of mix : C.M 1:4, (after dismantling the damaged & wetted portion and replastering to be done)	45.00	M2			
2	22.6 - Providing and laying water proofing treatment on roof slabs by applying cement slurry mixed with water proofing cement compound consisting of applying: a) after surface preparation, first layer of slurry of cement @0.488 kg/sqm mixed with water proofing cement compound @ 0.253 kg/sqm. b) laying second layer of fibre glass cloth when the first layer is still green. Overlaps of joints of fibre cloth should not be less than 10 cm. c) third layer of 1.5 mm thickness consisting of slurry of cement @ 1.289 kg/sqm mixed with water proofing cement compound @ 0.670 kg/sqm and coarse sand @ 1.289 kg/sqm. This will be allowed by water curing for 48 hours. d) fourth & final layer of plastering in CM 1:3, 12 mm or tiling with cement mortar (which will be paid separately). The entire treatment will be taken upto 30 cm on wall and tucked in to groove in the wall.	60.00	M2			
3	13.60.1 Finishing walls with Premium Acrylic emulsion paint with silicone additives of required shade : (Two or more coats applied @ 3.84 kg/10 sqm), on old surface, after scapping & cleaning etc. complete.	100.00	M2			

4	Painting: with synthetic enamel paint for existing doors and windows including priming coat and all cost etc complete, after scraping and cleaning the surface, on old one.	53.00	M2			
5	OD Engaging Carpenters for the maitanance of shutters of wooden doors and windows.	2.00	nos			
6	Structural Steel work in built up tubular ,16 guage (round, square or rectangular hollow tubes etc.) trusses etc., including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer, including welding and bolted with special shaped washers etc. complete. (16 gauge)	376.00	kg			
7	Providing and fixing 75 mm GI pipe as vertical supports for truss work including cutting, welding ,fixing in position with concrete and applying priming coat of approved steel primer including all cost etc complete	63.00	kg			
8	Providing and fixing 15 cm wide, pvc square pathy with steel brackets appropriate size, bolts, nuts and washers etc., including making necessary connections with rain water pipes complete.	66.00	M			
9	Supply and fixing rain water outlets, PVC 75 dia. (6 kg/cm2) Including jointing of pipes with one step PVC solvent cement and testing of joints as per the direction of Engineer in charge, including all cost etc. complete. Including end caps and end drops.	43.00	M			

10	Providing corrugated G.I. sheet roofing (powder coated) 0.35 mm thick, including vertical / curved surface fixed with polymer coated J or L hooks, bolts and nuts 8 mm diameter with bitumen and G.I. limpet washers or with G.I. limpet washers filled with white lead, including a coat of approved steel primer and two coats of approved paint on overlapping of sheets complete (up to any pitch in horizontal/ vertical or curved surfaces), excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required.	170.00	M2			
11	Extend the AC water pipe to outside from open terrace, using 32 mm diameter PVC pipe (6kg/cm2)	10.00	M			
	Total amount				Rs	
	GST 18 %				Rs	
	Grand total				Rs	
Contractor Regional Manager						